

## SPECIFICATION DATA SHEET | MODEL : 05TCG



The **TRANSCUBE™ 05TCG** is ideal for use in stand-by power applications and refueling for smaller equipment, such as industrial heaters, small generators, lighting towers... and more!

- ❖ **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- ❖ **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- ❖ **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
- ❖ **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- ❖ **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

### SPECIFICATIONS

**STANDARD FITTINGS:** High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.  
**OPTIONAL FITTINGS:** Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.

<b>Capacity (Brim-Fill) Litres:</b> 500	<b>Bund Material Thickness (in):</b> 1/8"
<b>Capacity (Brim-Fill) Imperial Gallons:</b> 110	<b>Inner Tank Material Thickness (in):</b> 1/8"
<b>Capacity (Brim-Fill) US Gallons:</b> 132	<b>Weight Empty (lbs/kg):</b> 965 lbs (437kg)
<b>Dimension Length (mm/in):</b> 1155 mm/45.25"	<b>Weight Full (lbs/kg):</b> 1901 lbs (862kg)
<b>Dimension Width (mm/in):</b> 1155 mm/45.25"	<b>Approvals:</b> UL142, ULC S-601-07, SUN IBC Type 31A,
<b>Dimension Height (mm/in):</b> 838 mm/33"	UN DOT, NFPA, Transport Canada, Vlare, Kiwa

