

## **SPECIFICATION DATA SHEET I** MODEL: 15ART-BLU



The Abbi Blue 15ART-BLU is a fully transportable storage tank that combines the benefits of fuel and DEF into one mobile unit. With separate compartments for fuel and DEF, the Abbi Blue enables safe and efficient refueling of tier 4 vehicles and machinery.

- Dual Compartments. With DEF's susceptibility to contamination, the Abbi Blue has a separate poly tank and pump cabinet for DEF to provide a closed environment for the fluid and eliminate the worry of cross contamination.
- Transportable. The Abbi Blue is UN DOT / TC approved to transport easily when full of fuel on your jobsite. Its all-in-one design and proven mobility enables fast and mobile handling of both fluids.
- **Environmentally Safe.** The Abbi Blue is double-walled and 110% contained to ensure the highest standards of safety. The dual cabinet design helps to ensure safe DEF handling and avoid any potential tier 4 machinery breakdowns or damage.
- Secure. The Abbi's large lockable equipment cabinet is capable of housing and protecting a variety equipment such as pumps and hose reels. This added protection helps to minimize the risk of equipment theft and vandalism.
- Accessible. Access manway enables easy access to the inner tank for routine cleaning and maintenance.

## **SPECIFICATIONS\***

Standard Tank Fittings: High accuracy contents gauge; 3" Fill point; 2" Fusible link fill port; 1" pump feed; Optional generator feed and return ports (1 set); Pressure/vacuum vent; Pump bracket; Breather vent; DEF tank in front cabinet. Optional Tank Fittings: Complete transfer pump kits; Water & particulate filter kits; (1) set of feed & return blocks; Fuel hose & quick couplers; Hose reel, 20UCA-EB (highway approved UniChassis trailer).

Capacity Litres (Fuel): 1,780 (brim-fill); 1,412 (safe-fill); 1,486 (optimum)	Capacity US Gallons (DEF): 42
Capacity US Gallons (Fuel): 470 (brim-fill); 373 (safe-fill); 393 (optimum)	Weight Empty (lbs/kg): 2,061 lbs (935kg)
Dimension Length (mm/in): 2270 mm/89.37"	Weight Full (lbs/kg): 5,337 lbs (2,421kg)
Dimension Width (mm/in): 1416 mm/55.75"	Approvals: UL 142, ULC-S601-07, UN DOT,
Dimension Height (mm/in): 1271.2 mm/50.05"	Transport Canada, NFPA 30, PPG2
Capacity Litres (DEF): 160	

<sup>\*</sup>Dimensions and weight do not include trailer. See H15ART-BLU-EB specification data sheet for combined tank & trailer specifications.



