

SPECIFICATION DATA SHEET | MODEL : FCP250



The **FUELCUBE** FCP250 is a compact, economic, double-walled fuel tank. Quickly and easily supply fuel where you need it, when you need it.

- ❖ **Transportable.** Forklift pockets and internal baffles designed to allow handling of the tank full of fuel. (Not DOT listed, but can be moved with Diesel fuel)
- ❖ **Stackable.** Easily stackable (2)-high empty to reduce storage space requirements.
- ❖ **Secure.** Pumps, and Equipment enclosed in lockable area – not need for additional pump “Lock-Box”.
- ❖ **Environmentally Safe.** Double-walled, 110% containment eliminates the need for additional spill pans, UL 142 approved.

SPECIFICATIONS

STANDARD FITTINGS: 1” Pump Feed, Lockable Pump/Equipment Cabinet, Heavy Duty Skid Base with Forklift Pockets, Vent, Fill Cap, UL Plate, Durable Marine Grade Paint Specification, Stacking Brackets.
 OPTIONAL FITTINGS: Direct Reading Float Gauge, 12v, 24v or 110 volt pump kits, Lifting slings, Hoses, Quick Couplers, Filters.

Capacity (Brim-Fill) Litres: 946	Outer Tank Material Thickness (in): 1/8”
Capacity (Brim-Fill) Imperial Gallons: 208	Inner Tank Material Thickness (in): 1/8”
Capacity (Brim-Fill) US Gallons: 250	Weight Empty (lbs/kg): 919 lbs (417kg)
Dimension Length (mm/in): 1143 mm/45”	Weight Full (lbs/kg): 3086 lbs (1400kg)
Dimension Width (mm/in): 1143 mm/45”	Approvals: UL142, ULC S-601-07, NFPA
Dimension Height (mm/in): 1260 mm/49.60”	
Dimension Cabinet Opening (mm/in): 836.6 mm x 533.4 mm/ 34” x 21”	

