






## SPECIFICATION DATA SHEET | Model: 30TCG



Extend the run times of your diesel powered equipment with the **TRANSCUBE™ 30TCG**.  
*Increased Efficiency + Decreased Expenses = Maximized Revenue.*

-  **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
-  **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
-  **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
-  **Efficient.** ENVIROconnect Equipment Cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

### SPECIFICATION

STANDARD FITTINGS:	High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.		
OPTIONAL EQUIPMENT:	Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.		
Capacity (brim full) Litres:	3,000	Bund Material Thickness (in):	1/8"
Capacity (brim full) Gallons (UK/US):	792	Inner Tank Material (thickness):	1/8"
Dimension Length (in):	91"	Weight Empty (Lbs):	2,153 lbs
Dimension Width (in):	60"	Weight Laden (Lbs):	7,765 lbs
Dimension Height (in):	52"	Design Approvals:	UL 142,
Dimension Cabinet Opening:	33½"W x 14" H		UN IBC Type 31A, US DOT