SPECIFICATION DATA SHEET | Model: 50TCG



The TRANSCUBE™ 50TCG is a versatile fuel deployment solution for larger diesel-powered equipment. With 1,240 gallons of back up fuel, your need for fuel truck visits is decreased, which in turn helps you to lower your carbon footprint and your expenses!

- Transportable. Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- Stackable. Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- Accessible. Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
- Efficient. ENVIRO connect Equipment Cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- Environmentally <u>Safe</u>. Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATION			
STANDARD FITTINGS: High accuracy contents gauge; 3"Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.			
OPTIONAL EQUIPMENT: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.			
Capacity (brim full) Litres:	4,700	Bund Material Thickness (in):	1/8"
Capacity (brim full) Gallons (UK/US):	1,240	Inner Tank Material (thickness):	1/8"
Dimension Length (in):	91"	Weight Empty (Lbs):	3,576 lbs
Dimension Width (in):	91"	Weight Laden (Lbs):	12,335 lbs
Dimension Height (in):	52"	Design Approvals:	UL142,
Dimension Cabinet Opening:	33½"W x 14" H		UN IBC Type 31A, US DOT